



# Floorseal Natural Stone Sealer Wet Look

NSSW-5 / NSSW-20

## DESCRIPTION

Natural Stone Sealer Wet Look is a breathable sealer which produces a sheen. Natural Stone Sealer Wet Look will slightly deepen the colour of natural stone, producing a slightly enriched colour with a sheen. Natural Stone Sealer Wet Look can be applied to sandstone, limestone, slate, clay-based tiles, and other porous surfaces such as concrete.

## USES

The sealing of porous:

- Natural stones i.e. sandstone
- Porous clay-based & cement-based block pavers.
- Concretes.

If in doubt, please call Floorseal Ltd on **01484 861461** or email [info@floorseal.co.uk](mailto:info@floorseal.co.uk) for guidance.

## ADVANTAGES

- Water based.
- Low odour.
- Rapid drying.
- Enhances colour.
- Attractive satin finish.
- Inhibits organic growth.

## COVERAGE

Approximately 20m<sup>2</sup> per litre



## DIRECTIONS OF USE

- Carry out a test in an inconspicuous area.
- If you find this product is not suitable for use on your project do not continue to use.
- All traces of grout or sand and cement mortars must be removed before sealing.
- If brush in compounds have been used, we recommend pre-cleaning with **Floorseal Sealer Residue Remover**.
- All surfaces are to be completely dry, do not apply if rain is likely in the next 24 hours.
- This product can be applied with a sprayer or paint pad in 2 consecutive **thin** applications. **Do not apply more than 2 coats.**
- We do not recommend using a roller.
- Apply a 2nd **lighter coat** within 60-90 minutes of the first application.
- Do not over apply this product, **thin coats** allow the product to cure and produces a favourable finish.
- Over application will result in white patches which are difficult to remove as the product is designed to be resilient.
- Ensure first application is touch dry before applying a 2nd **thin** coat.
- The product dries in approximately 2-4 hours but does not fully cure for 24 hours.
- In colder conditions the curing time can be longer.
- The surface will accept light foot traffic after around 3 hours.
- This product should only be applied when air temperatures are above 10°C and below 20°C.
- Safe for children, pets and wildlife when dry.
- If you wish to seal a previously sealed surface contact us for advice first.
- Do not apply to polished stone, glazed or non-porous surfaces.
- Do not place furniture back onto the sealed surface for 24 hours.
- The depth of colour achieved by this product will be dictated by the particular surface applied to & its porosity.
- Not suitable for faded black limestones.

## CONTRAINDICATIONS

- Do not apply to damp stone this will result in white patches forming.
- Apply in **thin** coats only. Do not apply in thick coats it does not create a 'wetter' & more durable finish.
- Do not use a roller.
- Allow adequate drying & curing time. Curing will take 24 hours when applied in the correct conditions.
- Not suited for sealing faded black limestone please use **Floorseal Black Limestone Restorer**.
- Will not adhere to non-porous or polished surfaces. i.e. glazed or polished porcelain.
- Do not place furniture back on the surface, or park vehicles on the surface for 24 hours.
- For sealing an interior surface, we recommend **Floorseal Stone & Tile Sealer Satin**.
- Do not apply over, or into other sealers. If you are considering applying to a previously sealed surface contact us for guidance.
- Pre clean with **Floorseal Sealer Residue Remover** if brush in compounds have been used.

Continues Overleaf



## PACKAGING

This product is non-flammable. Store in original container in a cool dry place, out of direct sunlight. Do not allow to freeze. Keep out of reach of children.

## SHELF LIFE

The maximum shelf life is 12 months. Use within 6 weeks of opening the product.

## PRODUCT DATA

<b>Appearance</b>	White / Opaque liquid.
<b>Ideal Application Conditions</b>	Very stable dry weather conditions.
<b>Dwell Time</b>	N/A
<b>Other Data</b>	Avoid cleaning the sealed surface with harsh cleaning chemicals.

## SAFETY PRECAUTIONS

Harmful if swallowed.  
 Causes serious eye irritation.  
 Keep out of reach of children.  
 Keep container tightly closed.  
 Do not get in eyes, on skin, or on clothing.  
 Wash skin thoroughly after handling.  
**IF SWALLOWED:** rinse mouth. Do NOT induce vomiting.  
**IF ON SKIN:** Gently wash with plenty of soap and water.  
**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If skin irritation or rash occurs: Get medical advice.



## ADDITIONAL USER INSTRUCTIONS

- Using a low-pressure pump-up sprayer in thin even coats produces a favourable finish.
- Using microfibre cloths soaked in the sealer helps the user produce thin even coats.



\*The information given in this product data sheet is given in good faith, based on current knowledge and experience. It relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process.

Such information is to the best of the company's knowledge and belief, accurate as of the date indicated. All recommendations are made without warranty or guarantee, as to accuracy, reliability or completeness since the conditions of use are beyond our control. It is the user's responsibility to satisfy themselves as to the suitability and application of such information for their own use.