



Floorseal Interior Brick Sealer & Dustproofers

SKU: IBSD

DESCRIPTION

Interior Brick Sealer & Dustproofers is a water based, low odour sealer and dustproofers. This product is suitable for sealing both interior brickwork and masonry, drying to an enhanced natural finish.

Interior Brick Sealer & Dustproofers is breathable and amazingly easy to apply with brush, roller, or sprayer. This product is a water-based non-flammable liquid therefore it is suitable for use around fireplaces. Matt finish on most surfaces but possible to build to a satin finish when applied in multiple coats.

USES

The sealing of:

- Interior porous clay-based brick.
- Sandblasted brick.
- Natural stones i.e. sandstone.

If in doubt, please call Floorseal Ltd on **01484 861461** or email info@floorseal.co.uk for guidance.

ADVANTAGES

- Water based.
- Low odour.
- Rapid dry.
- Deepens colour.
- Inhibits water & oil-based staining.
- Easy application.

COVERAGE

Approximately 8m² per litre (per coat).

DIRECTIONS OF USE

- **Carry out a test in an inconspicuous area.**
- **If you find this product is not suitable for use on your project do not continue to use.**
- All surfaces must be completely dry.
- Apply with a masonry style roller, brush, or sprayer.
- You may wish to apply a 2nd coat on very porous surfaces such as sandblasted brickwork.
- The product dries in approximately 1 hour but does not fully cure for 24 hours.
- This product should only be applied when air temperatures are above 10°C and below 23°C.
- Safe for children and pets once dry.
- If you wish to seal a previously sealed surface, contact us for advice first.
- Do not apply to polished, glazed or non-porous surfaces.
- Do not use on exterior surfaces.

CONTRAINDICATIONS

- Do not apply to damp surfaces.
- Please contact us for guidance if your wall has been sealed previously.
- If applied to a previously sealed surface which has not been stripped correctly the product may fail.
- Do not use in wet rooms/shower cubicles.
- Not for use on exterior surfaces.
- Do not use on non-porous surfaces like ceramic glazed tiles or porcelains.
- Use Ph neutral cleaners for everyday cleaning after the surface has been sealed.



Continues Overleaf



PACKAGING

This product is non-flammable. Store in original container in a cool dry place, out of direct sunlight. Do not allow to freeze. Keep out of reach of children.

SHELF LIFE

The maximum shelf life is 12 months. Please agitate periodically.

PRODUCT DATA

| | |
|-------------------------------------|---|
| Appearance | White/Opaque liquid. |
| Ideal Application Conditions | Totally dry unsealed surfaces which have been pre vacuumed. |
| Dwell Time | N/A |
| Other Data | Everyday cleaning should be carried out with Ph neutral cleaners. |

SAFETY PRECAUTIONS

Harmful if swallowed.
Causes serious eye irritation.
Keep out of reach of children.
Keep container tightly closed.
Do not get in eyes, on skin, or on clothing.
Wash skin thoroughly after handling.
IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
IF ON SKIN: Gently wash with plenty of soap and water.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If skin irritation or rash occurs: Get medical advice.



ADDITIONAL USER INSTRUCTIONS

- Always apply to totally dry surfaces.
- Leave adequate drying time after pre cleaning, more than 24 hours is often required on porous brick & porous stone.
- Vacuum all surfaces & particularly sandblasted surfaces before sealing.
- After 10 minutes wipe off any excess with microfibre cloths.
- Do not allow product build up or allow pooling.
- Use Ph neutral cleaners for aftercare cleaning i.e. **Floorseal Ph Neutral Floor Cleaner**.
- Can built up in 2 coats but the product may start to become visible on the surface.
- Expect a difference in appearance when applying to different kinds of brick or stone. This is not a paint!



*The information given in this product data sheet is given in good faith, based on current knowledge and experience. It relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process.

Such information is to the best of the company's knowledge and belief, accurate as of the date indicated. All recommendations are made without warranty or guarantee, as to accuracy, reliability or completeness since the conditions of use are beyond our control. It is the user's responsibility to satisfy themselves as to the suitability and application of such information for their own use.