



Floorseal Indian Sandstone Sealer & Colour Intensifier

SKU:ISSCI

DESCRIPTION

Indian Sandstone Sealer & Colour Intensifier is designed to both seal and slightly enhance colourful sandstones. Indian Sandstone Sealer & Colour Intensifier will accentuate natural shades and earthy colours in Indian sandstone & Yorkstone. This includes rainbow sandstones, Raj sandstones & colourful Yorkshire sandstone slabs.

Indian Sandstone Sealer will dry to a slightly enhanced matt finish. Indian Sandstone Sealer & Colour Intensifier will not trap moisture as it is 100% breathable.

USES

The sealing of:

- Indian sandstone
- Yorkshire sandstone.
- Porous clay-based & cement-based block pavers.
- Porous clay-based tiles.

If in doubt, please call Floorseal Ltd on **01484 861461** or email info@floorseal.co.uk for guidance.

ADVANTAGES

- Breathable.
- Accentuates colour.
- Low odour.
- Water based.
- Rapid dry.
- No moisture clouding.
- No trapped moisture.
- Suitable for listed properties.

COVERAGE

Approximately 8m² per litre (16m² for a 2nd application).

DIRECTIONS OF USE

- **Carry out a test in an inconspicuous area.**
- **If you find this product is not suitable for use on your project do not continue to use.**
- All traces of grout or sand and cement mortars must be removed before sealing.
- For internal applications turn off underfloor heating systems and allow the surface to cool.
- If brush in compounds have been used, pre-clean with **Floorseal Sealer Residue Remover** (for exterior surfaces).
- Pre clean interior floors with **Floorseal Stone Floor Cleaner**.
- All surfaces must be completely dry, do not apply if rain is likely in the next 24 hours.
- Apply with a masonry style roller, paint pad or sprayer in conjunction with microfibre cloths.
- Apply one coat to saturation. It is important to saturate the surface and allow the product to soak in.
- Remove all visible excess with microfibre cloths, you must not allow any product to dry on the surface.
- The removal of excess product must be carried out within no more than 20 -30 minutes (this time can be extended in cooler conditions).
- You should apply a 2nd light coat around 40 minutes later (wet on wet), remove all visible excess as before.
- Do not apply the first & second applications on separate days, the first application will have already cured.
- We recommend working in small sections.
- The product dries in approximately 2 hours but does not fully cure for 24 hours.
- This product should only be applied when air temperatures are above 10°C and below 20°C.
- Safe for children, pets, and wildlife when dry.
- If you wish to seal a previously sealed surface, contact us for advice first.
- Do not apply to polished stone, glazed or non-porous surfaces.

CONTRAINDICATIONS

- This product will not accentuate or create colour interest in flat grey sandstones i.e. Kandla greys.
- Do not apply over or into other sealers. If you wish to seal a previously sealed surface contact us for guidance.
- Not removing any excess product will lead to oxidation. This process of excess removal must be carried out.
- Do not apply to damp stone or if rain is likely.
- Do not apply to non-porous surfaces.

Continues Overleaf



PACKAGING

This product is non-flammable. Store in original container in a cool dry place, out of direct sunlight. Do not allow to freeze. Keep out of reach of children.

SHELF LIFE

It is preferable to use this product within 2 months of the purchase date. If this product is to be stored please agitate periodically. The maximum shelf life is 12 months. Use within 6 weeks of opening.

PRODUCT DATA

Appearance	White/Opaque liquid.
Ideal Application Conditions	Totally dry stone. Dry conditions required during curing. Full sun is not preferable for application.
Dwell Time	N/A
Other Data	Avoid harsh cleaning agents for maintenance cleaning.

SAFETY PRECAUTIONS

Harmful if swallowed.
Causes skin irritation.
Causes serious eye irritation.
Wear protective gloves.
IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
IF ON SKIN: Gently wash with plenty of soap and water.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If exposed or if you feel unwell: Call a POISON CENTRE or doctor.
If skin irritation persists: Get medical advice.
If eye irritation persists: Get medical advice.



ADDITIONAL USER INSTRUCTIONS

- Adding multiple coats does not necessarily increase depth of colour.
- Adding more product than 2 subsequent applications may be possible on very porous stone. We recommend this is carried on the same day you begin the sealing process on.
- Do not seal on separate days, the first application will have already cured.
- The lifespan of this product is approximately 4-5 years.
- It may be possible to reapply the product as the porosity of the stone returns in time.
- It is possible to pressure wash your patio (after this sealer is fully cured) for annual cleaning.
- Curing time will vary from 8 hours to 24 hours. This is dependent on air temperatures & humidity.
- Sealing in higher air temperatures could hinder the products ability to penetrate the surface of the stone. It will make excess removal problematical due to premature drying.
- This product will produce differences in appearance depending on the type (or subcategory) of stone. This product is not paint!



*The information given in this product data sheet is given in good faith, based on current knowledge and experience. It relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process.

Such information is to the best of the company's knowledge and belief, accurate as of the date indicated. All recommendations are made without warranty or guarantee, as to accuracy, reliability or completeness since the conditions of use are beyond our control. It is the user's responsibility to satisfy themselves as to the suitability and application of such information for their own use.