



# Floorseal Porcelain Tile Sealer For Patios

SKU:PTSP

## DESCRIPTION

Porcelain Tile Sealer For Patios is a breathable topical sealer suitable for most porcelains. It is a water based, low odour product which resists water & oil-based staining.

Porcelain Tile Sealer For Patios is a durable sealer which resists scratches & only requires one thin coat to protect porcelain tiles. This durable sealer can also slightly deepen surface colours, enriching the colour within the tile. A resilient finish with a shine, suitable for external & internal tiles.

## USES

The sealing of:

- Porcelain tiles which require sealing with a sheen.
- Can be used on interior floors.

If in doubt, please call Floorseal Ltd on **01484 861461** or email [info@floorseal.co.uk](mailto:info@floorseal.co.uk) for guidance.

## ADVANTAGES

- Water based, so low odour.
- One coat application.
- Breathable.
- Deepens surface colours to darker porcelains.

## COVERAGE

Approximately 15m<sup>2</sup> - 25m<sup>2</sup> per litre.



## DIRECTIONS OF USE

- Carry out a test in an inconspicuous area.
- If you find this product is not suitable for use on your project do not continue to use.
- Remove all traces of grout or sand and cement mortars before sealing.
- If brush in compounds have been used pre-clean with **Floorseal Sealer Residue Remover** first.
- All surfaces must be completely dry, do not apply if rain is likely in the next 24 hours.
- Apply with a microfibre flat mop or microfibre cloths, do not spray, roller or brush this product onto the surface.
- Apply in one thin coat ensuring the product is applied neatly.
- Do not allow puddling, a thin wet and even coat must be maintained.
- It is imperative the product is applied carefully as it will be difficult to remove once dry.
- The product dries in approximately 2 hours but does not fully cure for 24 hours.
- Do not walk on the surface for a minimum of 2 hours after application.
- Do not place patio furniture back onto the tiles for 48 hours.
- This product should only be applied when air temperatures are above 10°C and below 20°C.
- Safe for children, pets, and wildlife when dry.
- Do not apply to polished porcelains.

## CONTRAINDICATIONS

- Only apply in one coat only.
- Only apply with a microfibre cloth or flat microfibre mop.
- Test on a small area to check suitability.
- Only apply to totally dry tiles in dry conditions.
- Do not use a roller.
- Do not allow the product to puddle.
- Do not place furniture back on the sealed surface for 48 hours.
- Some slip resistance will be lost after application.

Continues Overleaf



## PACKAGING

This product is non-flammable. Store in original container in a cool dry place, out of direct sunlight. Do not allow to freeze. Keep out of reach of children.

## SHELF LIFE

The maximum shelf life is 6 months. Use the product within 6 weeks of opening.

## PRODUCT DATA

<b>Appearance</b>	Opaque liquid.
<b>Ideal Application Conditions</b>	Dry conditions with no rain forecast.
<b>Dwell Time</b>	N/A
<b>Other Data</b>	Avoid cleaning the sealed surface with harsh chemicals.

## SAFETY PRECAUTIONS

Harmful if swallowed.  
Causes serious eye irritation.  
Keep out of reach of children.  
Keep container tightly closed.  
Do not get in eyes, on skin, or on clothing.  
Wash skin thoroughly after handling.  
**IF SWALLOWED:** rinse mouth. Do NOT induce vomiting.  
**IF ON SKIN:** Gently wash with plenty of soap and water.  
**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If skin irritation or rash occurs: Get medical advice.



## ADDITIONAL USER INSTRUCTIONS

- Do not apply in more than one coat as it will lead to over application problems.
- Apply with microfibre cloths or a microfibre flat mop.
- It is imperative the product is applied in a thin even coat.



\*The information given in this product data sheet is given in good faith, based on current knowledge and experience. It relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process.

Such information is to the best of the company's knowledge and belief, accurate as of the date indicated. All recommendations are made without warranty or guarantee, as to accuracy, reliability or completeness since the conditions of use are beyond our control. It is the user's responsibility to satisfy themselves as to the suitability and application of such information for their own use.