



# Floorseal Block Paving Eco Seal

SKU: BKES

## DESCRIPTION

Floorseal Block Paving Eco Seal is an easy to use water-based sealer. This product can be applied to old or newly laid cement/concrete-based block pavers. This sealer will seal the surface of the paver and harden sanded joints, thus inhibiting organic growth and staining. Free from solvents & VOCs, so fume free with a rapid dry formula. This product seals & protects block paving whilst producing an attractive natural finish. Can be applied in a single coat or two coats for more porous surfaces.

## USES

The sealing of porous:

- Cement-based block pavers.
- Concrete-based block pavers.

If in doubt, please call Floorseal Ltd on **01484 861461** or email [info@floorseal.co.uk](mailto:info@floorseal.co.uk) for guidance.

## ADVANTAGES

- Water based.
- Low odour.
- Rapid drying.
- Subtle colour enhancement.
- Inhibits organic growth.
- Resists staining.
- Hardens sanded joints.

## COVERAGE

Approximately 2m<sup>2</sup> per litre (1st coat). 5m<sup>2</sup> per litre (2nd coat where required).

\*The coverage rate will vary due to the level of porosity encountered.

## DIRECTIONS OF USE

- Carry out a test in an inconspicuous area.
- If you find this product is not suitable for use on your project do not continue to use.
- Pre-clean older surfaces with **Floorseal Block Paving Intensive Cleaner**.
- Once dry, treat the block & joint with **\*Floorseal Algae Remover Concentrate**.
- Allow to dry (we recommend 48 hours).
- Apply the sealer when rain is not likely in the next 24 hours.
- Apply the sealer via a sprayer, watering can or roller in 2 applications.
- The 1st coat should be applied liberally, soaking the block & particularly sanded joints.
- Squeegee or roller over the surface & into the joints.
- Redistribute any pooling or puddling over the surface.
- No pools or puddles should be left on the surface.
- Apply the 2nd coat (where required) two hours later.
- The sealer should be applied more sparingly and distributed over the surface.
- Squeegee or roller over the surface.
- No pooling or puddling should be noted after the product is applied.
- Do not place furniture or park cars on the surface for at least 24 hours after sealing.
- The product fully dries in approximately 4 hours but does not fully cure for 24 hours.
- This product should only be applied when air temperatures are above 10°C and below 20°C.
- If you wish to seal a previously sealed surface contact us for advice first.
- Do not apply to clay-based block pavers or other surfaces.
- \*Use Floorseal Algae Remover Concentrate as an ongoing cleaner.

## CONTRAINDICATIONS

- Do not apply to damp surfaces this will result in white patches forming.
- Allow adequate drying & curing time.
- Curing will take 24 hours when applied in the correct conditions.
- Do not place furniture back on the surface, or park vehicles on the surface for 24 hours.
- Do not apply over, or into other sealers. If you are considering applying to a previously sealed surface contact us for guidance.
- Do not apply if rain is likely.
- Pre-clean existing/older block pavers with Floorseal Block Paving Intensive Cleaner for deep cleaning.
- Use Floorseal Algae Remover Concentrate as a follow up cleaner (& ongoing cleaner) to suppress weeds, algae and moss.

## PACKAGING

This product is non-flammable. Store in original container in a cool dry place, out of direct sunlight. Do not allow to freeze. Keep out of reach of children.

Continues Overleaf



## SHELF LIFE

The maximum shelf life is 12 months. Use within 6 weeks of opening the product.

## PRODUCT DATA

<b>Appearance</b>	White / Opaque liquid.
<b>Ideal Application Conditions</b>	Very stable dry weather conditions.
<b>Dwell Time</b>	N/A
<b>Other Data</b>	Once sealed avoid cleaning the sealed surface with harsh cleaning chemicals.

## SAFETY PRECAUTIONS

Harmful if swallowed.  
Causes serious eye irritation.  
Keep out of reach of children.  
Keep container tightly closed.  
Do not get in eyes, on skin, or on clothing.  
Wash skin thoroughly after handling.  
**IF SWALLOWED:** rinse mouth. Do NOT induce vomiting.  
**IF ON SKIN:** Gently wash with plenty of soap and water.  
**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If skin irritation or rash occurs: Get medical advice.



## ADDITIONAL USER INSTRUCTIONS

- Adjust the coverage rate to suit the level of porosity found on site.
- If brush in compounds have been used you will use less product than pavers with sanded joints.
- If resin based brush in compounds have been used pre-clean with Floorseal Sealer Residue Remover.



\*The information given in this product data sheet is given in good faith, based on current knowledge and experience. It relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process.

Such information is to the best of the company's knowledge and belief, accurate as of the date indicated. All recommendations are made without warranty or guarantee, as to accuracy, reliability or completeness since the conditions of use are beyond our control. It is the user's responsibility to satisfy themselves as to the suitability and application of such information for their own use.