



Floorseal Natural Stone Sealer Breathe

SKU: NSSB

DESCRIPTION

Natural Stone Sealer Breathe is an impregnating breathable sealer for all natural stones. This sealer is for waterproofing natural stone against water and oil-based staining, whilst retaining a totally natural appearance.

It is suitable for all porous natural stone, clay-based tiles, and brickwork. This product can be applied to old, weathered stone or newly laid stone, it will not trap moisture as it is 100% breathable. Two applications will provide full protection.

USES

The sealing of porous:

- Natural stones i.e. sandstone.
- Porous clay-based & cement-based block pavers.
- Concretes.
- Brickwork.
- Can be used as a pre sealer.

If in doubt, please call Floorseal Ltd on **01484 861461** or email info@floorseal.co.uk for guidance.

ADVANTAGES

- A fully breathable impregnating sealer.
- Suitable for listed buildings.
- Suitable for sealing rubble filled walls.
- Does not trap moisture.
- Surfaces will retain a totally natural unaltered appearance.
- Resists water & oil-based staining.
- Inhibits organic growth.
- Suitable for interior or exterior surfaces.

COVERAGE

Approximately 8m² per litre (16m² for a 2nd application).

DIRECTIONS OF USE

- **Carry out a test in an inconspicuous area.**
- **If you find this product is not suitable for use on your project do not continue to use.**
- All traces of grout or sand and cement mortars must be removed before sealing.
- If brush in compounds have been used, pre-clean with **Floorseal Sealer Residue Remover** first.
- All surfaces must be completely dry, do not apply if rain is likely in the next 24 hours.
- Apply with a masonry style roller, paint pad or sprayer in conjunction with microfibre cloths.
- Apply one coat to saturation. It is important to fully saturate the surface & allow the product to sink in.
- Remove all visible excess with microfibre cloths, you must not allow any product to dry on the surface.
- You should apply a 2nd light coat around 40 minutes after the first (wet on wet) remove all excess as before. Do not apply the first & second applications on separate days, the first application will have already cured.
- Always remove the excess product within 20-30 minutes.
- The product dries in approximately 2 hours but does not fully cure for 24 hours.
- This product should only be applied when air temperatures are above 10°C and below 20°C.
- Safe for children, pets, and wildlife when dry.
- If you wish to seal a previously sealed surface, contact us for advice first.
- Do not apply to polished stone, glazed or non-porous surfaces.
- Also suitable to use as a pre-sealer.

CONTRAINdicATIONS

- Do not attempt to seal into or over a surface which has been previously sealed.
- If you are attempting to seal a surface which has been previously been sealed, please contact us for guidance.
- Please use **Floorseal Sealer Residue Remover** if you have used brush in compounds.
- Do not apply to damp stone.
- Always apply to refusal by saturating the surface, then remove all excess with microfibre cloths. Not removing the excess can cause white patches to form on the surface.
- Always apply a 2nd application on the same day as the first - preferably within 40 minutes.
- Do not apply if rain is likely. The product will need 24 hours to fully cure in dry conditions.

Continues Overleaf



PACKAGING

This product is non-flammable. Store in original container in a cool dry place, out of direct sunlight. Do not allow to freeze. Keep out of reach of children.

SHELF LIFE

The maximum shelf life is 12 months.

PRODUCT DATA

Ideal Application Conditions	Dry warm conditions without rain forecast.
Dwell Time	N/A
Other Data	Avoid cleaning the sealed surface with harsh chemicals i.e. acids & strong alkaline solutions.

SAFETY PRECAUTIONS

May cause an allergic skin reaction.
Keep out of reach of children.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Wear protective gloves/protective clothing/eye protection/face protection.
IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.
Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion: Wash out mouth with water. Consult a doctor.
Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.



ADDITIONAL USER INSTRUCTIONS

- When applying a 2nd treatment, please complete within approximately 40 minutes after the first.
- If more than 12 hours has elapsed since the first treatment it may be difficult for additional sealer to penetrate. The first treatment will have cured creating surface tension.



*The information given in this product data sheet is given in good faith, based on current knowledge and experience. It relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process.

Such information is to the best of the company's knowledge and belief, accurate as of the date indicated. All recommendations are made without warranty or guarantee, as to accuracy, reliability or completeness since the conditions of use are beyond our control. It is the user's responsibility to satisfy themselves as to the suitability and application of such information for their own use.