



Floorseal Black Limestone Restorer

SKU: BLR

DESCRIPTION

Black Limestone Restorer is designed to both seal and colour enhance natural black limestones. Black limestone becomes deeper and richer in colour when sealed with this product. Black Limestone Restorer dries to a natural breathable matt finish. This product can also be applied to blue & grey limestone & other porous surfaces which benefit from deeper colour & shading. One application is sufficient to both protect & colour enhance the treated surface.

USES

The sealing of porous:

- Black limestone.
- Grey limestone.
- Blue limestones.

If in doubt, please call Floorseal Ltd on **01484 861461** or email info@floorseal.co.uk for guidance.

ADVANTAGES

- This product is a fully breathable impregnator.
- Deepens colour to restore fading.
- Only one single application is required.
- Powerful resistance to water & oil-based staining.
- Inhibits organic growth.
- Can be applied to new and older stone.

COVERAGE

Approximately 30m² per litre.



DIRECTIONS OF USE

- Carry out a test in an inconspicuous area.
- If you find this product is not suitable for use on your project do not continue to use.
- Make sure all residues from grout, brush in compound or sand & cement mortars are removed before sealing.
- For interior use - switch off underfloor heating systems 24 hours before use.
- For exterior use pre-clean with Floorseal Sealer Residue Remover (if you have used a brush in compound).
- For interior floors pre-clean with Floorseal Stone Floor Cleaner (rinse well after use).
- All surfaces must be completely dry, do not apply if rain is likely in the next 48 hours.
- Apply with in one single application with a brush, roller, microfibre cloth/ flat mop or a paint pad.
- Only work in small sections of a 3-4m² at a time (before removing excess product).
- Allow the product to penetrate the surface for a **maximum** of 5-10 minutes. Adjust based on air temperatures.
- After no more than 5-10 minutes thoroughly buff the surface dry to fully remove all excess product.
- Remove all excess product **within** 5-10 minutes of applying the sealer.
- The product is to be applied and allowed to penetrate the surface - **ALL EXCESS IS THEN TO BE REMOVED. Do not apply and simply leave the product to dry on the surface!**
- Black Limestone Restorer dries in approximately 1 hour but does not fully cure for 48 hours.
- Should only be applied when air temperatures are above 10°C and below 20°C.
- Safe for children, pets and wildlife when dry.
- If you are considering applying this product to a surface previously sealed contact us for guidance.
- Do not apply to non-porous, polished or glazed surfaces. **Not suitable for slate.**

CONTRAINDICATIONS

- Do not apply to damp stone, the stone can become patchy/white.
- Do not apply into or onto other sealers.
- If your stone has been sealed before, please contact us for guidance before using this product.
- Always remove the excess, if you do not do so the product will oxidise on the surface and turn white.
- Ensure the sealer can cure in dry conditions for at least 48 hours - do not apply if rain is likely!
- Do not apply in full sun or when air temperatures are above 20 degrees Celsius. The product will dry before penetrating the stone allowing it to dry on the surface.
- Do not apply in temperatures under 10 degrees Celsius or the product will not cure.
- Apply once, adding additional product is more likely to lead to difficulty removing the excess. It does not necessarily deepen the colour further.
- Pay particular care when applying to polished black limestones due to increased surface tension.
- Not to be used on slate.

Continues Overleaf



PACKAGING

This product is non-flammable. Store in original container in a cool dry place, out of direct sunlight. Keep out of reach of children.

SHELF LIFE

The maximum shelf life is 24 months.

PRODUCT DATA

| | |
|-------------------------------------|---|
| Ideal Application Conditions | Totally dry conditions with no rain for 48 hours. |
| Dwell Time | N/A |
| Other Data | Excess removal is critical! |

SAFETY PRECAUTIONS

Harmful if swallowed.
Causes skin irritation.
Causes serious eye irritation.
Harmful to aquatic life with long lasting effects.
Keep out of reach of children.
Avoid breathing fumes.
Do not get in eyes, on skin, or on clothing.
Wear protective gloves.
IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
IF ON SKIN: Gently wash with plenty of soap and water.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or if you feel unwell: Call a POISON CENTRE or doctor.



ADDITIONAL USER INSTRUCTIONS

- The easiest way to remove the excess product is with microfibre cloths.
- Have plenty of microfibre cloths once damp – discard.
- Work in small sections of a few square metres only, so you can reach into the area and remove the excess more easily.
- Using Floorseal Sealer Residue Remover helps the product penetrate into the surface. It removes the invisible resinous compounds from brush in or sweep in style compounds.
- Leave adequate drying time after cleaning 12 hours is often not enough. We recommend 48 hours or more.
- We recommend contacting us prior to using this product for advice.



*The information given in this product data sheet is given in good faith, based on current knowledge and experience. It relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process.

Such information is to the best of the company's knowledge and belief, accurate as of the date indicated. All recommendations are made without warranty or guarantee, as to accuracy, reliability or completeness since the conditions of use are beyond our control. It is the user's responsibility to satisfy themselves as to the suitability and application of such information for their own use.