(FLOORSEAL) RENDER CLEANER SOFTWASH SOLUTION

Page: 1

Compilation date: 22/03/2023

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: (FLOORSEAL) RENDER CLEANER SOFTWASH SOLUTION Product code: RCSWS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC35: Washing and cleaning products (including solvent based products).

1.3. Details of the supplier of the safety data sheet

Company name: FLOORSEAL LIMITED

Unit N7, Meltham Mills Industrial Estate Knowle Lane, Meltham Holmfirth West Yorkshire HD9 4DS UK GB & NI Tel: 01484 861 461

Email: info@floorseal.co.uk

1.4. Emergency telephone number

Emergency tel: 01484 861 461

(office hours only)

Section 2: Hazards identification-

2.1. Classification of the substance or mixture

Classification under CLP:	Skin Corr. 1B: H314; Aquatic Acute 1: H400; -: EUH031
Most important adverse effects:	Contact with acids liberates toxic gas. Causes severe skin burns and eye damage. Very
	toxic to aquatic life.

2.2. Label elements

Label elements:	
Hazard statements:	EUH031: Contact with acids liberates toxic gas.
	H314: Causes severe skin burns and eye damage.
	H400: Very toxic to aquatic life.
Hazard pictograms:	GHS05: Corrosion
	GHS09: Environmental
	\wedge \wedge



[cont...]

(FLOORSEAL) RENDER CLEANER SOFTWASH SOLUTION

		. age
Signal words:	Danger	
Precautionary statements:	P102: Keep out of reach of children.	
	P260: Do not breathe spray.	
	P280: Wear protective gloves/protective clothing/eye protection/face protection.	
	P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting	
	P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.	
	Rinse skin with water.	
	P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for	
	breathing.	
	P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove	Э
	contact lenses, if present and easy to do. Continue rinsing.	
	P405: Store locked up.	
Haz. ingredients (label):	Contains:	
	SODIUM HYPOCHLORITE	
2.3. Other hazards		

2.3. Other hazards

Other hazards: Contact with acids liberates very toxic gas.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

SODIUM HYPOCHLORITE SOLUTION CL ACTIVE - REACH registered number(s): 01-2119488154-34

EINECS	CAS	PBT / WEL	CLP Classification	Percent
231-668-3	7681-52-9	-	Skin Corr. 1B: H314; Eye Dam. 1: H318; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; -: EUH031	1-10%

Non-classified ingredients:

PRIMARY ALCOHOL ETHOXYLATE C9-11 6 MOLE - REACH registered number(s): 01-2119980051-45-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent	
-	68439-46-3	-	Acute Tox. 4: H302; Eye Dam. 1: H318	<1%	
SODIUM BICAF	RBONATE - REA	CH registered number(s): 01-21194576	606-32-xxxx		
205-633-8	144-55-8	-	-	<1%	
SODIUM CARBONATE - REACH registered number(s): 01-2119485498-19					
207-838-8	497-19-8	-	Eye Irrit. 2: H319	<1%	

Section 4: First aid measures

Page: 2

(FLOORSEAL) RENDER CLEANER SOFTWASH SOLUTION

4.1. Description of first aid me	easures
Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin.
	Drench the affected skin with running water for 10 minutes or longer if substance is still
	on skin. Transfer to hospital if there are burns or symptoms of poisoning.
Eye contact:	Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist
	examination.
Ingestion:	Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10
	minutes. Transfer to hospital as soon as possible.
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. Move to
	fresh air in case of accidental inhalation of vapours. Consult a doctor.
4.2. Most important symptoms	s and effects, both acute and delayed
	Blistering may occur. Progressive ulceration will occur if treatment is not immediate.
	Corneal burns may occur. May cause permanent damage.
-	Corrosive burns may appear around the lips. Blood may be vomited. There may be
ingeonom	bleeding from the mouth or nose.
Inhalation:	There may be shortness of breath with a burning sensation in the throat. Exposure may
	cause coughing or wheezing.
Delaved / immediate effects:	Immediate effects can be expected after short-term exposure.
	ate medical attention and special treatment needed
Immediate / special treatment:	Eye bathing equipment should be available on the premises.
	Lye batting equipment should be available on the premises.
Section 5: Fire-fighting measure	
Section 5: Fire-fighting measure	
Section 5: Fire-fighting measu	ures
Section 5: Fire-fighting measures	ures Suitable extinguishing media for the surrounding fire should be used. Use water spray
5.1. Extinguishing media Extinguishing media	Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.
Section 5: Fire-fighting measu	Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.
Section 5: Fire-fighting measure 5.1. Extinguishing media Extinguishing media: 5.2. Special hazards arising fr	Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.
5.1. Extinguishing media Extinguishing media Extinguishing media: 5.2. Special hazards arising fr	Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.
Section 5: Fire-fighting measu 5.1. Extinguishing media Extinguishing media: 5.2. Special hazards arising fr	ures Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers. rom the substance or mixture Corrosive. In combustion emits toxic fumes. Water based product. Advice relates to dry
Section 5: Fire-fighting measures 5.1. Extinguishing media Extinguishing media: 5.2. Special hazards arising fr Exposure hazards: 5.3. Advice for fire-fighters	ures Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers. com the substance or mixture Corrosive. In combustion emits toxic fumes. Water based product. Advice relates to dry residues after water has evaporated.
Section 5: Fire-fighting measures 5.1. Extinguishing media Extinguishing media: 5.2. Special hazards arising fr Exposure hazards: 5.3. Advice for fire-fighters	ures Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers. om the substance or mixture Corrosive. In combustion emits toxic fumes. Water based product. Advice relates to dry residues after water has evaporated. Wear self-contained breathing apparatus. Wear protective clothing to prevent contact
Section 5: Fire-fighting measure 5.1. Extinguishing media Extinguishing media: 5.2. Special hazards arising fr Exposure hazards: 5.3. Advice for fire-fighters Advice for fire-fighters:	ures Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers. com the substance or mixture Corrosive. In combustion emits toxic fumes. Water based product. Advice relates to dry residues after water has evaporated. Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.
Section 5: Fire-fighting measures 5.1. Extinguishing media Extinguishing media: 5.2. Special hazards arising fr Exposure hazards: 5.3. Advice for fire-fighters Advice for fire-fighters: Section 6: Accidental release	ures Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers. com the substance or mixture Corrosive. In combustion emits toxic fumes. Water based product. Advice relates to dry residues after water has evaporated. Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes. measures
Section 5: Fire-fighting measures 5.1. Extinguishing media Extinguishing media: 5.2. Special hazards arising fr Exposure hazards: 5.3. Advice for fire-fighters Advice for fire-fighters: Section 6: Accidental release	ures Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers. com the substance or mixture Corrosive. In combustion emits toxic fumes. Water based product. Advice relates to dry residues after water has evaporated. Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.
Section 5: Fire-fighting measures 5.1. Extinguishing media Extinguishing media: 5.2. Special hazards arising fr Exposure hazards: 5.3. Advice for fire-fighters Advice for fire-fighters: Section 6: Accidental release 6.1. Personal precautions, pro-	ures Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers. com the substance or mixture Corrosive. In combustion emits toxic fumes. Water based product. Advice relates to dry residues after water has evaporated. Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes. measures
Section 5: Fire-fighting measures 5.1. Extinguishing media Extinguishing media: 5.2. Special hazards arising fr Exposure hazards: 5.3. Advice for fire-fighters Advice for fire-fighters: Section 6: Accidental release 6.1. Personal precautions, pro-	ures Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers. com the substance or mixture Corrosive. In combustion emits toxic fumes. Water based product. Advice relates to dry residues after water has evaporated. Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes. measures Detective equipment and emergency procedures

(FLOORSEAL) RENDER CLEANER SOFTWASH SOLUTION

clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Wash the spillage site with large amounts of water.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area.		
Respiratory protection:	Self-contained breathing apparatus must be available in case of emergency.		
Hand protection:	Impermeable gloves.		
Eye protection:	Tightly fitting safety goggles. Ensure eye bath is to hand.		
Skin protection:	Impermeable protective clothing.		
Environmental:	Prevent from entering in public sewers or the immediate environment.		

(FLOORSEAL) RENDER CLEANER SOFTWASH SOLUTION

Page: 5

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties				
State:	Liquid			
Colour:	Pale yellow			
Odour:	Characteristic odour			
Evaporation rate:	Slow			
Viscosity:	Non-viscous			
Boiling point/range°C:	100	Melting point/range°C:	0	
Flammability limits %: lower:	Not applicable.	upper:	Not applicable.	
Flash point°C:	Not applicable.	Part.coeff. n-octanol/water:	Not applicable.	
Autoflammability°C:	Not applicable.	Vapour pressure:	Not applicable.	
Relative density:	1.180	pH:	11.5 - 12.5	
VOC g/l:	0			

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids. Strong reducing agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes. Contact with acids liberates very toxic gas.

Section 11: Toxicological information

11.1. Information on toxicological effects

(FLOORSEAL) RENDER CLEANER SOFTWASH SOLUTION

Page: 6

Hazardous ingredients:

SODIUM HYPOCHLORITE SOLUTION...100% CL ACTIVE

ORL MUS	LD50	5800	mg/kg
---------	------	------	-------

Non-classified ingredients:

PRIMARY ALCOHOL ETHOXYLATE C9-11 6 MOLE

IHL	RAT	LC50	>5	mg/l
ORL	RAT	LD50	200-2000	mg/kg
SKN	RAT	LD50	>2000	mg/kg

SODIUM BICARBONATE

ORL	BT	LD50	4220	mg/Kg
-----	----	------	------	-------

SODIUM CARBONATE

ORL	MUS	LD50	6600	mg/kg
ORL	RAT	LD50	4090	mg/kg
SCU	MUS	LD50	2210	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

- **Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.
- **Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

(FLOORSEAL) RENDER CLEANER SOFTWASH SOLUTION

				Page:	
PRIMARY ALCOHOL ETHO	XYLATE C9-11 6 MOLE				
FISH		96H LC50	1-10	mg/l	
SODIUM BICARBONATE					
FATHEAD MINNOWS		96H LC50	8600	g/l	
Ecotoxicity values:	No data available.				
12.2. Persistence and degrada	ability				
Persistence and degradability:	Not biodegradable. The surfactant(s) contained in this preparation complies (comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents.				
12.3. Bioaccumulative potenti	al				
Bioaccumulative potential:	No bioaccumulation potential.				
12.4. Mobility in soil					
Mobility:	Readily absorbed into soil. Volatile. Soluble in water.				
12.5. Results of PBT and vPvI	B assessment				
PBT identification:	This product is not identifi	ied as a PBT/vPvB sub	ostance.		
12.6. Other adverse effects					
Other adverse effects:	Very toxic to aquatic organisms.				
ection 13: Disposal conside	rations				
13.1. Waste treatment method	ls				
Disposal operations:	Transfer to a suitable con	tainer and arrange for	collection by specialis	ed disposal	
	company.				
Recovery operations:	Not applicable.				
Waste code number:	20 01 29				
Disposal of packaging:	Dispose of as normal indu	ustrial waste. Clean wi	th water.		
NB:	The user's attention is drawn to the possible existence of regional or national				
	regulations regarding disp	oosal.			
ection 14: Transport information	ation				

14.1. UN number

UN number: UN1760

14.2. UN proper shipping name

Shipping name: CORROSIVE LIQUID, N.O.S.

(SODIUM HYPOCHLORITE SOLUTION...5-10% CL ACTIVE)

(FLOORSEAL) RENDER CLEANER SOFTWASH SOLUTION

Page: 8 14.3. Transport hazard class(es) Transport class: 8 14.4. Packing group Packing group: III 14.5. Environmental hazards Environmentally hazardous: Yes Marine pollutant: No 14.6. Special precautions for user Special precautions: No special precautions. Tunnel code: E Transport category: 3 Section 15: Regulatory information 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Specific regulations: Not applicable. **15.2. Chemical Safety Assessment** Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier. Section 16: Other information Other information Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830. All substances in this preparation are registered within UK/EU/EFTA countries under the REACH (UK/EC) (ammended) regulations, EC 1907/2006 Product requires CRC (child resistant closure) and TDW (tactile danger warning) for retail sale to the general public. Detergent Regulations EC648/2004, the product contains amongst other ingredients:-Chlorine based bleaching agents 5-15%. IMPORTANT NOTE: Risk phases in this section below relate to the INDIVIDUAL COMPONENTS in the formulation when used at their FULL CONCENTRATIONS, and not at the reduced levels in the mixed product.

See sections 2 and 3 for the calculated hazard and risk phrases for the blended product. Phrases used in s.2 and s.3: EUH031: Contact with acids liberates toxic gas. H302: Harmful if swallowed. H314: Causes severe skin burns and eye damage. H318: Causes serious eye damage.

(FLOORSEAL) RENDER CLEANER SOFTWASH SOLUTION

H319: Causes serious eye irritation.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. **Page:** 9