



Floorseal Sandstone Wet Look Sealer

SKU: SADE

DESCRIPTION

Suitable for new or old interior/exterior sandstone slabs, patios, pavers & paths. Produces a colour enhanced invigorated silk finish. Suitable for naturally colourful & also relatively plain/monotone sandstone slabs. Sandstone Wet Look Sealer strongly resists moisture clouding, UV light, abrasion, damp penetration, dirt, grime & organic growth.

USES

The sealing of porous:

- Colourful natural sandstone
- Plain coloured sandstones
- Slate, concrete & clay pavers
- Other porous natural stone

If in doubt, please call Floorseal Ltd on **01484 861461** or email info@floorseal.co.uk for guidance.

ADVANTAGES

- Rapid drying
- Enhances colour
- Attractive invigorated finish
- Inhibits organic growth
- Easy application
- Resists liquid staining
- Strongly resists moisture clouding
- Suitable for highly porous natural stone
- Resists degradation by UV light
- Resists abrasion

COVERAGE

12m² per litre depending on the porosity & type of surface.

DIRECTIONS OF USE

- **Carry out a test in an inconspicuous area to check for suitability.**
- Only apply to clean dry surfaces which do not display efflorescence.
- The surface should be free from residues/hazes of grout, mortar & resins etc.
- If the surface has been deep cleaned/pressure washed allow 3-5 days drying before sealing.
- Exterior surfaces – for optimal results apply via a low pressure sprayer.
- Interior surfaces – apply via short pile roller or brush.
- Allow first coat to dry for 2 hours before applying second coat (if required).
- Do not allow to pool/puddle, redistribute/remove any puddling with a dry roller or cloth.
- For virgin newly laid stone, you may require 2 coats.
- For older/dense or previously sealed stone, a single coat is optimal.
- Do not walk in your work/application area (wet sealer) whilst applying.
- Working small sections produces optimal results.
- Newly laid patios should be allowed to settle and dry for 4-8 weeks before sealing.
- Apply when air temps are above 12°C & below 24°C.
- Do not apply if rain is likely in the next 24 hours.
- If you wish to seal a previously sealed surface, contact us for advice first.
- If applied indoors, switch off underfloor heating 24 hours before application.
- Not to be applied to highly polished stone or non-porous surfaces such as porcelain.
- When working indoors ventilate the area during & after application.

CONTRAINDICATIONS

- Allow adequate drying & curing time. The product dries rapidly, full curing will take 24 hours
- Will not adhere to non-porous or fully polished reflective surfaces i.e. porcelains. Do not use in wet rooms
- Do not place furniture back on the surface, or park vehicles on the surface for at least 24 hours
- If you are applying to a surface previously sealed with a different brand/type of product contact us for guidance
- Do not apply to recently laid surfaces, allow 4-8 weeks for the surface to settle & dry before application
- Do not apply to damp surfaces or surfaces which display efflorescence
- Do not walk in your work/application area (wet sealer) whilst applying
- Do not pressure wash for 7 days after application
- Test before use, to gauge the effect of this product on your particular surface
- When working indoors ventilate the area during & after use
- Do not use as a pre-grout sealer

Continues Overleaf



PACKAGING

This product is non-flammable. Store in original container in a cool dry place, out of direct sunlight. Do not allow to freeze. Keep out of reach of children.

SHELF LIFE

The maximum shelf life is 24 months when stored correctly. Please agitate periodically.

PRODUCT DATA

| | |
|-------------------------------------|--|
| Ideal Application Conditions | Stable dry weather. |
| Dwell Time | N/A |
| Other Data | Avoid cleaning the sealed surface with harsh cleaning chemicals. |

SAFETY PRECAUTIONS

Harmful if swallowed. Causes serious eye irritation.
 Keep out of reach of children.
 Keep container tightly closed. Do not get in eyes, on skin, or on clothing.
 Wash skin thoroughly after handling.
IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
IF ON SKIN: Gently wash with plenty of soap and water.
IF IN EYES: Rinse cautiously with water for several minutes.
 Remove contact lenses, if present and easy to do.
 Continue rinsing.
 If skin irritation or rash occurs: Get medical advice.



ADDITIONAL USER INSTRUCTIONS

- Test first and allow to fully dry to assess the suitability of this product for your sealing project
- Please note the level of colour enhancement will be based on the natural colour displayed within the stone
- Naturally colourful sandstone will deepen in colour to a greater degree than a plain grey sandstone
- Brushes & rollers can be cleaned (whilst still wet with product) with white spirit
- Sprayers can be rinsed through with white spirit followed by warm water & detergent



*The information given in this product data sheet is given in good faith, based on current knowledge and experience. It relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process.

Such information is to the best of the company's knowledge and belief, accurate as of the date indicated. All recommendations are made without warranty or guarantee, as to accuracy, reliability or completeness since the conditions of use are beyond our control. It is the user's responsibility to satisfy themselves as to the suitability and application of such information for their own use.