



Floorseal Exterior Wood Sealer

SKU: WODS

DESCRIPTION

Exterior Wood Sealer is a subsurface sealer & preserver for exterior wood. Suitable for use to seal sheds, fences, tables, chairs, workshops & decking with an invisible protective seal.

This natural wood sealer creates a powerful water repellent surface, it is highly resistant to UV light & moisture penetration. The application of this product extends the lifespan of exterior wood by inhibiting the growth and staining of moulds & algae.

Highly suited when sealing surfaces located in damp climates and shaded areas. Can be applied to softwood or hardwood to resist rotting and warping. Apply to Oak, Beech, Pine, Red Cedar, Douglas Fir & more. Up to 10 years protection from the elements.

USES

The sealing of:

- Softwood.
- Hardwood.
- Wooden Decking, Sheds & Garden Rooms.
- Outdoor Wooden Furniture.

If in doubt, please call Floorseal Ltd on **01484 861461** or email **info@floorseal.co.uk** for guidance.

ADVANTAGES

- A fully breathable penetrating sealer.
- Surfaces retain an unaltered appearance.
- Resists water & damp penetration.
- Inhibits organic growth.
- Suitable exterior surfaces.
- Solvent free, does not contain VOCs.
- Can be used on most exterior wood.
- Makes maintenance easier.
- Resists organic growth.

COVERAGE

Approximately 5m² per litre (per coat).

DIRECTIONS OF USE

- Carry out a test in an inconspicuous area. If you find this product is not suitable for use on your project, do not continue to use.
- Apply to dry porous wooden surfaces with a brush, roller or low-pressure sprayer.
- Apply x2 coats, the 2nd coat ideally applied within 3 hours of the first coat.
- During application work any run-off back into the surface with a brush.
- Apply to dry surfaces when air temperatures are above 10°C & below 24°C.
- Do not apply if rain is forecast in the next 4 hours.
- Surfaces can be pre-treated with Floorseal Green Remover Concentrate a few days prior to sealing and treated with thereafter.
- Softwoods will require more sealer than hardwoods.
- This product should not be over painted.

CONTRAINDICATIONS

- Do not apply to damp surfaces.
- Do not apply if rain is likely within 4 hours of application.
- Do not dilute.
- Always test before committing to full application.
- Do not over paint this product.



Continues Overleaf



PACKAGING

This product is non-flammable. Store in original container in a cool dry place, out of direct sunlight. Do not allow to freeze or become unduly hot. Keep out of reach of children.

SHELF LIFE

The maximum shelf life is 12 months.

PRODUCT DATA

Ideal Application Conditions	Dry conditions.
Dwell Time	N/A
Other Data	Avoid cleaning the sealed surface with harsh chemicals.

SAFETY PRECAUTIONS

Skin contact: Wash immediately with plenty of soap and water.
Eye contact: Bathe the eye with running water for 15 minutes.
Ingestion: Wash out mouth with water.
Inhalation: Consult a doctor.
Skin contact: There may be mild irritation at the site of contact.
Eye contact: There may be irritation and redness.
Ingestion: There may be irritation
Inhalation: No symptoms.
Wear protective gloves/protective clothing/ eye protection/face protection.
Keep out of reach of children.



ADDITIONAL USER INSTRUCTIONS

- When sealing very dense surfaces work in small areas to ensure all excess product is removed before it dries.
- Tools and implements may be cleaned with warm soapy water. But please note this product is a waterproofing agent so some materials will permanently repel liquid after use.
- Adapt the coverage rate based on the porosity of the wood being treated i.e. hardwoods will require less sealer than a softwood.
- Always test the product before committing to full application.
- Shake the container before use.
- Surfaces can be maintained by periodically applying Floorseal Green Remover Concentrate.



*The information given in this product data sheet is given in good faith, based on current knowledge and experience. It relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process.

Such information is to the best of the company's knowledge and belief, accurate as of the date indicated. All recommendations are made without warranty or guarantee, as to accuracy, reliability or completeness since the conditions of use are beyond our control. It is the user's responsibility to satisfy themselves as to the suitability and application of such information for their own use.