



# Floorseal Stone Floor Cleaner

SKU: SFC

## DESCRIPTION

Stone Floor Cleaner is a powerful & economical water-based cleaning solution for the removal of dirt and grime. It will easily remove ingrained dirt, grime, oils, grease and wax.

Suitable for sandstone, slate, granite, quartz, porcelain, ceramics & clay-based tiles. Also suitable for honed marble, limestone, basalt & travertine. Stone Floor Cleaner is for deep cleaning the surface of natural stone floors & associated mortar/grouted joints (including lime pointing). This acid free product deep cleans contemporary stone floors & natural stone flooring located in historic buildings. Can also be used to strip water-based acrylic topical sealers.

## USES

The cleaning of:

- Natural stones i.e. sandstone/limestone/York stone.
- Porous clay-based & cement-based block pavers.
- Concretes.
- Brickwork.
- Terracotta.
- Quarry Tile.
- Porcelain.
- Victorian Tiles.
- Terrazzo.

If in doubt, please call Floorseal Ltd on **01484 861461** or email [info@floorseal.co.uk](mailto:info@floorseal.co.uk) for guidance.

## ADVANTAGES

- Deep cleans.
- Non-acidic blend.
- Use prior to sealing with one of our Floorseal sealers.
- Removes old waxes.
- Cleans & degreases.
- Removes ingrained dirt.

## COVERAGE

10m<sup>2</sup> per litre (after dilution).

## DIRECTIONS OF USE

- **Carry out a test in an inconspicuous area to ensure suitability & coverage.**
- **If you find this product is not suitable for your project, do not continue to use.**
- Switch off underfloor heating at least 12 hours before cleaning.
- Dilute at 1:5 with warm water (one part product to five parts water).
- The rate of dilution can be increased or decreased to suit the level of contamination encountered (subject to testing).
- Apply with a mop or brush.
- Can also be used in conjunction with rotary machines.
- Allow to dwell for 10-15 minutes, lightly agitate with a brush or mop for best results.
- Do not allow to dry out during the dwell time, to prevent this from occurring add more product.
- Rinse away with plenty of clean water and allow to dry.
- Repeat as required.
- You may wish to mask off any surrounding varnished, painted or sensitive surfaces the product might encounter.
- If the product encounters sensitive surfaces rinse/wipe the product away promptly.
- Safe for children & pets when dry.
- Coverage rates will ultimately be dictated by surface porosity, level of soiling & dilution rate.

## CONTRAINDICATIONS

- Do not apply to painted, varnished, or metallic surfaces.
- If the product encounters sensitive surfaces, wipe the product away promptly.
- Neutralise the floor after use by rinsing liberally with water.
- Do not apply topical surface coatings onto a surface that has not been rinsed and neutralised.
- Not for the removal of cement/grout haze/residues.
- Does not strip solvent based acrylic topcoats or polyurethane.

## PACKAGING

This product is non-flammable. Store in original container in a cool dry place, out of direct sunlight. Do not allow to freeze or become unduly hot. Keep out of reach of children.

Continues Overleaf



## SHELF LIFE

The maximum shelf life is 12 months.

## PRODUCT DATA

Ideal Application Conditions	Totally dry surfaces.
Dwell Time	10-15 minutes.
Other Data	Neutralise with clean water.

## SAFETY PRECAUTIONS

**Keep out of reach of children. Do not breathe dust/fumes/gas/mist/vapours/spray. Wear protective gloves/protective clothing/eye protection/face protection.**  
**IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting.  
**IF ON SKIN (or hair):** Take off immediately all contaminated clothing. Rinse skin with water [or shower]. Remove person to fresh air and keep comfortable for breathing.  
**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
**Contains Sodium Hydroxide.**



## ADDITIONAL USER INSTRUCTIONS



\*The information given in this product data sheet is given in good faith, based on current knowledge and experience. It relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process.

Such information is to the best of the company's knowledge and belief, accurate as of the date indicated. All recommendations are made without warranty or guarantee, as to accuracy, reliability or completeness since the conditions of use are beyond our control. It is the user's responsibility to satisfy themselves as to the suitability and application of such information for their own use.