



# Floorseal Outdoor Porcelain Tile Cleaner

SKU: ODPC

## DESCRIPTION

Floorseal Outdoor Porcelain Tile Cleaner is an effective cleaning solution for just laid external porcelain tiles. This product will remove cement-based staining, mortar splashes, fresh efflorescence salting & leachate staining.

Suitable for use as a general builders cleaning solution, just after porcelain tiling has been installed. Perfect for removing general cement-based stains, cement-based grout hazing, leachate staining, fresh efflorescence salting, mortar splashes, concrete hazing & cement dust.

## USES

The cleaning of external:

- Porcelain.
- Acid resistant natural stones.
- Clay-based tiles or pavers.

If in doubt, please call Floorseal Ltd on **01484 861461** or email [info@floorseal.co.uk](mailto:info@floorseal.co.uk) for guidance.

## ADVANTAGES

- Easy to use water-based deep cleaning solution for just laid exterior porcelains.
- Removes cement-based slurry primers, cement-based grouts and general cement staining.
- Rapid action.
- Low fuming.
- Powerful formula.

## COVERAGE

Approximately 5m<sup>2</sup> per litre

Coverage rates vary dependant on porosity and level of contamination encountered.

## DIRECTIONS OF USE

- **Do not apply to acid sensitive surfaces like limestone, travertine, marble, & basalt.**
- **Carry out a test in an inconspicuous area. If you find this product is not suitable for use on your project, do not continue to use.**
- Typically applied undiluted, but can be diluted for mild hazing (subject to testing).
- Apply liberally with a sprayer, plastic watering can, plastic bucket or directly from the container.
- Allow to briefly dwell on the surface.
- Agitate with a stiff brush & rinse off thoroughly within a few minutes.
- Do not allow the product to dry on the surface (add more product to prevent this when required).
- After cleaning, rinse the area treated with liberal amounts of clean water.
- Repeat as required.
- For optimal results pressure wash the tiles to complete the process.
- Safe for children, pets & wildlife when dry.
- **NOT suitable for the removal of resin-based compounds, resin-based grout or epoxy grout/pigments.**
- Do **NOT** apply to acid sensitive surfaces & metals.
- Coverage rates will vary depending on surface type, porosity & level of soiling.

## CONTRAINDICATIONS

- Do not apply to acid sensitive surfaces.
- This product will not remove **resin-based** grout hazes or resin-based brush in compounds.
- Does not remove thick coatings/crusts of cement, concrete, mortar or grout staining after it has cured.
- Does not remove slurry primers mixed with SBR.

## PACKAGING

This product is non-flammable. Store in original container in a cool dry place, out of direct sunlight. Do not allow to freeze or become unduly hot. Keep out of reach of children.

## SHELF LIFE

The maximum shelf life is 12 months.

Continues Overleaf



## PRODUCT DATA

<b>Ideal Application Conditions</b>	Cool conditions.
<b>Dwell Time</b>	A few minutes. Rinse well after use.
<b>Other Data</b>	Neutralise with clean water.

## SAFETY PRECAUTIONS

Keep out of reach of children.  
Do not breathe dust/fumes/gas/mist/vapours/spray.  
Wear protective gloves/protective clothing/eye protection/face protection.  
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
Contains: PHOSPHORIC ACID; HYDROCHLORIC ACID



## ADDITIONAL USER INSTRUCTIONS

- Adjust the ratio of solution so it is effective on the level of contamination encountered.
- It is the user's responsibility to check whether the surface being treated is not acid sensitive. Do not apply to acid sensitive surfaces.



\*The information given in this product data sheet is given in good faith, based on current knowledge and experience. It relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process.

Such information is to the best of the company's knowledge and belief, accurate as of the date indicated. All recommendations are made without warranty or guarantee, as to accuracy, reliability or completeness since the conditions of use are beyond our control. It is the user's responsibility to satisfy themselves as to the suitability and application of such information for their own use.