



Floorseal Indian Sandstone Sealer & Colour Intensifier

SKU:ISSCI

DESCRIPTION

Indian Sandstone Sealer & Colour Intensifier is designed to seal against staining & produce a subtle colour enhanced finish. This water-based impregnating sealer will accentuate natural hues and earthy colours contained with naturally colourful Indian sandstone & York stone. This includes rainbow sandstones, Raj sandstones, York sandstone & other forms of sandstones. Indian

Sandstone Sealer & Colour Intensifier will dry to a subtle colour enhanced natural/matt finish. This product will not trap moisture as it is 100% breathable. Typically used as an exterior sealer but can also be used on interior floors.

USES

The sealing of:

- Indian sandstone.
- Yorkshire sandstone.
- Naturally colourful sandstone.

If in doubt, please call Floorseal Ltd on **01484 861461** or email info@floorseal.co.uk for guidance.

ADVANTAGES

- Breathable.
- Accentuates colour.
- Low odour.
- Water based.
- Rapid dry.
- Will not moisture cloud..
- Will not trapped moisture.
- Compatible with brush in compounds.
- Compatible with traditional mortars/jointing systems.
- Does not create a sheen.
- Natural matt finish.

COVERAGE

Approximately 8m² per litre (16m² for a 2nd application).

DIRECTIONS OF USE

- Carry out a test in an inconspicuous area. If you find this product is not suitable for use on your project, do not continue to use.
- Ensure the surface is clean & free from contaminations of grout & mortar.
- If resin-based brush in compounds have been used, pre-clean the surface with Floorseal Sealer Residue Remover & rinse off.
- All surfaces must be completely dry, do not apply if rain is likely within 24 hours.
- Apply with a masonry style roller or low-pressure garden sprayer.
- Apply one coat liberally to fully saturate the stone.
- Remove all visible areas of excess sealer after approximately 30 minutes.
- Carry out excess sealer removal with microfibre cloths or a dry masonry roller.
- Apply a 2nd lighter coat approximately 40 minutes after the first, remove all visible excess as before.
- Dries rapidly & cures over 24 hours.
- Apply when air temperatures are above 10°C and below 24°C.
- This product is compatible with brush in compounds & traditional mortars or grout.
- Do not apply to non-porous surfaces.
- Not suitable for Kandla Grey sandstone or monotone/plain sandstone which do not display natural colour (when dry).
- Not suitable for use as a pre-grout sealer.

CONTRAINDICATIONS

- This product will not accentuate or create colour interest in monotone/grey sandstones such as Kandla Grey.
- Do not apply over or into surface sealers. If you wish to seal a previously sealed surface contact us for guidance.
- Not removing any excess product will lead to oxidation. This process of excess removal must be carried out.
- Do not apply to damp stone or if rain is likely.
- Do not apply to non-porous surfaces.

Continues Overleaf



PACKAGING

This product is non-flammable. Store in original container in a cool dry place, out of direct sunlight. Do not allow to freeze or become unduly hot. Keep out of reach of children.

SHELF LIFE

It is preferable to use this product within 2 months of the purchase date. If this product is to be stored please agitate periodically. The maximum shelf life is 12 months. Use within 6 weeks of opening.

PRODUCT DATA

Ideal Application Conditions	Dry stone. Dry conditions are required during curing. Full sun is not preferable for application.
Dwell Time	N/A
Other Data	Can be reapplied without the need for stripping.

SAFETY PRECAUTIONS

Skin contact: Wash immediately with plenty of soap and water.
There may be mild irritation at the site of contact.
Eye contact: Bathe the eye with running water for 15 minutes.
There may be irritation and redness.
Ingestion: Wash out mouth with water.
Inhalation: No symptoms.
Wear protective gloves/protective clothing/eye protection/face protection.
Keep out of reach of children.



ADDITIONAL USER INSTRUCTIONS

- Adding multiple coats does not necessarily increase depth of colour.
- Adding more product than 2 subsequent applications may be possible on very porous stone.
- The lifespan of this product is approximately 4-5 years.
- It is possible to pressure wash your patio (after this sealer is fully cured) for annual cleaning.
- Curing time will vary from 6 hours to 24 hours. This is dependent on air temperatures & humidity.
- Sealing in very high air temperatures could hinder the products ability to penetrate the surface of the stone.
- This product will produce differences in appearance depending on the type (or subcategory) of stone. This product is not paint!



*The information given in this product data sheet is given in good faith, based on current knowledge and experience. It relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process.

Such information is to the best of the company's knowledge and belief, accurate as of the date indicated. All recommendations are made without warranty or guarantee, as to accuracy, reliability or completeness since the conditions of use are beyond our control. It is the user's responsibility to satisfy themselves as to the suitability and application of such information for their own use.