



Floorseal Hard Floor Cleaner & Degreaser

SKU: HSCD

DESCRIPTION

Hard Floor Cleaner & Degreaser is suitable for general cleaning and degreasing of hard floors & general work surfaces. Suitable for use on concrete, safety flooring, vinyl flooring, stone & tiled floors.

This product is a powerful cleaning solution to remove dirt, grime and degrease commercial & domestic flooring. Can also be used as a surface cleaner to clean general metals & plastics. Adjust the dilution rate to suit the level of contamination found on site. Can be used as an everyday cleaner for wooden flooring coated with varnishes or epoxy finishes.

USES

The cleaning & degreasing of:

- Concrete
- Stone
- Porcelain
- Clay tiles
- Metals
- Wood (when finished with polyurethane or epoxy)
- Work tops
- Metalwork in kitchens.
- Vinyl including Altro, Karndean & Amtico
- Plastics including UPVC

If in doubt, please call Floorseal Ltd on **01484 861461** or email info@floorseal.co.uk for guidance.

ADVANTAGES

- Can be used with hand held sprayers.
- Can be used in mop & buckets.
- Can be used in conjunction with rotary machines.
- Can be used in conjunction with scrubber driers.
- Use on floors, walls, & appliances.
- Unperfumed.
- Cleans & degreases.

COVERAGE

Dependant on the level of contamination & surface type.

DIRECTIONS OF USE

- Carry out a test in an inconspicuous area.
- If you find this product is not suitable for use on your project do not continue to use.
- For daily cleaning dilute at a ratio of 1:20 (200ml diluted into 4 litres of warm water).
- For intensive cleaning dilute at a ratio of 1:4 (1 litre diluted into 4 litres of warm water).
- Apply to the surface and agitate.
- Rinse away with clean water after a few minutes.
- For really grimy surfaces keep the surface wet with product for up to 10 minutes.
- Always rinse away with clean water.
- Suitable for use with mop & bucket systems.
- Can be used in conjunction with scrubber driers or rotary machines.
- Can be used in hand held sprayers for cleaning general work surfaces & metals.

CONTRAINdicATIONS

- Use warm water, **not** very hot water.
- Not suitable for stripping floor polishes.
- Do not use on waxed or oiled wood floors.



Continues Overleaf



PACKAGING

This product is non-flammable. Store in original container in a cool dry place, out of direct sunlight. Do not allow to freeze or become unduly hot. Keep out of reach of children.

SHELF LIFE

The maximum shelf life is 24 months.

PRODUCT DATA

Ideal Application Conditions	Normal interior temperatures.
Dwell Time	1 - 10 minutes.
Other Data	Dilute into warm water.

SAFETY PRECAUTIONS

Wear protective gloves/protective clothing/eye protection/face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF ON SKIN: Gently wash with plenty of soap and water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.



ADDITIONAL USER INSTRUCTIONS

- Ultimately the dilution rate can be adjusted to suit the degree of surface contamination.
- 1:20 is a typical dilution rate.
- 1:4 is a dilution rate suited to the removal of heavier contaminations.
- The product can be used undiluted.
- Always rinse well with clean water.
- Can be used on wooden flooring if polyurethane varnishes or epoxy coatings have been applied.



*The information given in this product data sheet is given in good faith, based on current knowledge and experience. It relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process.

Such information is to the best of the company's knowledge and belief, accurate as of the date indicated. All recommendations are made without warranty or guarantee, as to accuracy, reliability or completeness since the conditions of use are beyond our control. It is the user's responsibility to satisfy themselves as to the suitability and application of such information for their own use.