



Floorseal Natural Stone Sealer Breathe

SKU: NSSB

DESCRIPTION

Natural Stone Sealer Breathe is a impregnating breathable sealer for all natural stones. This sealer creates a water repellent surface to protect natural stone against water and oil-based staining, whilst retaining a totally natural appearance.

The product is suitable for all porous natural stone, clay-based tiles, and brickwork. This product can be applied to old, weathered stone or newly laid stone, it is a breathable product which does not trap moisture. Two applications will provide full protection.

USES

The sealing of porous:

- Natural stones i.e. sandstone.
- Porous clay-based & cement-based block pavers.
- Concretes.
- Brickwork.
- Pre-grout sealing.

If in doubt, please call Floorseal Ltd on **01484 861461** or email info@floorseal.co.uk for guidance.

ADVANTAGES

- A fully breathable impregnating sealer.
- VOC Free.
- Suitable for listed buildings.
- Suitable for sealing rubble filled walls.
- Does not trap moisture.
- Treated surfaces retain their natural unaltered appearance.
- Resists water & oil-based staining.
- Inhibits organic growth.
- Suitable for interior or exterior surfaces.
- Can be applied to floors without a DPM fitted.
- Aids ongoing maintenance.
- Unaltered appearance.
- Water-based.

COVERAGE

Approximately 8m² per litre (16m² for a 2nd application).

DIRECTIONS OF USE

- **Carry out a test in an inconspicuous area. If you find this product is not suitable for use on your project, do not continue to use.**
- Apply to clean & dry surfaces only.
- Do not apply if rain is likely in the next 24 hours.
- Ensure surfaces are free from grout/mortar/compound residues before sealing.
- Apply with a masonry style roller, paint pad or sprayer.
- Apply one coat to saturation, allow the product to sink in.
- Fully remove all visible excess with microfibre cloths, do not allow the product to dry on the surface.
- Apply a 2nd light coat approximately 40 minutes after the first, remove all excess as before.
- Always remove the excess product within 20-30 minutes.
- The product dries in approximately 2 hours but does not fully cure for 24 hours.
- Also suitable for use as a pre-sealer.
- If pre-sealing, apply the product once and wait 24hrs before grouting. Once grouted, allow 48 hours before the 2nd application is carried out.
- This product should only be applied when air temperatures are above 10°C and below 24°C.
- Safe for children, pets, and wildlife when dry.
- If you wish to seal a surface previously sealed with a different type/brand of product contact us for advice.
- Do not apply to fully polished stone, glazed or non-porous surfaces.
- Do not dilute.

CONTRAINDICATIONS

- Failing to remove excess product can cause white patches to form.
- Do not apply to damp stone/tiles or grout.

PACKAGING

This product is non-flammable. Store in original container in a cool dry place, out of direct sunlight. Do not allow to freeze or become unduly hot. Keep out of reach of children.

SHELF LIFE

The maximum shelf life is 12 months.

Continues Overleaf



PRODUCT DATA

Ideal Application Conditions	Dry warm conditions without rain forecast.
Dwell Time	N/A
Other Data	Avoid cleaning the sealed surface with harsh chemicals.

SAFETY PRECAUTIONS

Skin contact: Wash immediately with plenty of soap and water.
Eye contact: Bathe the eye with running water for 15 minutes.
Ingestion: Wash out mouth with water.
Inhalation: Consult a doctor.
Wear protective gloves/protective clothing/ eye protection/face protection.
Keep out of reach of children.



ADDITIONAL USER INSTRUCTIONS

- Always apply to refusal by saturating the surface, remove all excess with microfibre cloths.
- Pre-clean the surface with Floorseal Sealer Residue Remover if you have used brush in compounds.
- The surface can be pressure washed after sealing for ongoing maintenance. Or cleaned with one of our cleaning agents.



*The information given in this product data sheet is given in good faith, based on current knowledge and experience. It relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process.

Such information is to the best of the company's knowledge and belief, accurate as of the date indicated. All recommendations are made without warranty or guarantee, as to accuracy, reliability or completeness since the conditions of use are beyond our control. It is the user's responsibility to satisfy themselves as to the suitability and application of such information for their own use.