



Floorseal Premium Stone Enhancer

SKU: PENR

DESCRIPTION

Premium Stone Enhancer is a powerful colour enhancer suitable for porous natural stone such as, colourful sandstone, limestone, porous granite, brick, masonry and tiles. This product is a breathable impregnating sealer which dries to a deeply enhanced natural matt finish.

A single application is all that is required to seal & enhance your surface.

Always test for suitability before use and adhere to the instructions on both the label and associated Technical Data Sheets.

This is a powerful colour enhancer and will be difficult to remove if used incorrectly. If unsure on the correct method of application or suitability, please contact Floorseal Ltd for further advice.

USES

The sealing of porous:

- Black/blue/grey limestone.
- Colourful sandstone.
- Clay based tiles.
- Bricks.
- Unpolished granite

If in doubt, please call Floorseal Ltd on **01484 861461** or email info@floorseal.co.uk for guidance.

ADVANTAGES

- This product is a fully breathable impregnator.
- Deepens colour to enrich surfaces or restore fading.
- Only one application of product is required.
- Powerful resistance to water & oil-based staining.
- Inhibits organic growth.
- Can be applied to new or older surfaces.
- Large coverage per litre of product.

COVERAGE

Approximately 30m² (one coat only).

DIRECTIONS OF USE

- **Carry out a test in an inconspicuous area. If you find this product is not suitable for use on your project, do not continue to use.**
- Make sure all residues/hazing of grout, brush in compound or sand & cement mortars are removed before sealing.
- For interior use switch off underfloor heating systems and allow to cool.
- For exterior surfaces pre-clean with Floorseal Sealer Residue Remover, if you have used a brush in compound.
- If the surface has been cleaned allow at least 48 hours drying time before sealing.
- All surfaces are to be completely dry, do not apply if rain is likely in the next 48 hours.
- Apply once onto small sections (a few square metres at a time) using either a brush, roller, paint pad, or microfibre cloth/flat mop.
- Allow the product to penetrate the surface for a maximum of 5-10 minutes. Adjust this figure based on air temperature and test patches.
- After a maximum of 5-10 minutes thoroughly buff the surface by hand with dry microfibre cloths to fully remove excess product. Not only pooling, but all traces of liquid sealer remaining on the surface. After excess removal the surface should have a natural/matt appearance.
- Never apply and simply leave the product to dry on the surface.
- Premium Stone Enhancer dries in approximately 2 - 4 hours but does not fully cure for 48 hours.
- Should only be applied when air temperatures are above 10°C and below 20°C.
- If you are considering applying this product to a surface which has previously been sealed, contact us for guidance.
- Do not apply to non-porous, polished, glazed surfaces or dilute with other liquids.
- Not suitable for slate, monotone grey sandstone or Kandla grey/monotone sandstone.

CONTRAINDICATIONS

- Do not apply to damp stone, if you do so the surface can become patchy/white.
- Do not apply into or onto other sealers. Do not dilute.
- Always remove the excess, if you do not do so this can lead to failure.
- The surface should be dry for 48 hours before use. Ensure the sealer can cure in dry conditions - do not apply if rain is likely!
- Do not apply in full sun or when air temperatures are above 20 degrees Celsius. The product may dry before penetrating the stone.
- Do not apply in temperatures under 10 degrees Celsius or the product will not cure.
- Apply once, adding additional product is more likely to lead to difficulty removing the excess.

Continues Overleaf



CONTRAINDICATIONS (continued)

- Do not apply to polished or non-porous surfaces.
- Not suitable for slate, monotone grey stone or Kandla Grey sandstone.
- Do not assume that enhancers replicate total saturation with water.
- Test before use!

PACKAGING

This product is flammable. Store in original container in a cool dry place, out of direct sunlight. Do not allow to freeze or become unduly hot. Keep out of reach of children.

SHELF LIFE

The maximum shelf life is 24 months.

PRODUCT DATA

Ideal Application Conditions	Totally dry conditions with no rain for 48 hours.
Dwell Time	N/A
Other Data	Excess removal is critical!

SAFETY PRECAUTIONS

Harmful if swallowed. Causes serious eye irritation.
 Keep out of reach of children.
 Keep container tightly closed.
 Do not get in eyes, on skin, or on clothing.
 Wash skin thoroughly after handling.
 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
 IF ON SKIN: Gently wash with plenty of soap and water.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If skin irritation or rash occurs: Get medical advice.
 Flammable.



ADDITIONAL USER INSTRUCTIONS

- Have plenty of microfibre cloths, once damp with product - discard.
- Work in small sections of a few square metres only. This ensures you can reach into the work area and remove the excess quickly.
- Discard any rollers or cloths after use.
- Test before use!



*The information given in this product data sheet is given in good faith, based on current knowledge and experience. It relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process.

Such information is to the best of the company's knowledge and belief, accurate as of the date indicated. All recommendations are made without warranty or guarantee, as to accuracy, reliability or completeness since the conditions of use are beyond our control. It is the user's responsibility to satisfy themselves as to the suitability and application of such information for their own use.